

HARDWARE FEATURES

Standards and Protocols	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.1q, IEEE 802.1p
Interface	8 10/100/1000Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Fan Quantity	Fanless
Power Supply	External Power Adapter(Output: 9VDC/0.6A)
Power Consumption	Maximum: 4.48W (220V/50Hz)
Dimensions (W x D x H)	6.2*4.0*1.0 in. (158*101*25 mm)

PERFORMANCE

Switching Capacity	16Gbps
Packet Forwarding Rate	11.9Mpps
MAC Address Table	4K
Packet Buffer Memory	1.5Mb
Jumbo Frame	15KB

SOFTWARE FEATURES

Quality of Service	Support Port-based/802.1p/DSCP priority Support 4 priority queues Rate Limit Storm Control
L2 Features	IGMP Snooping V1/V2/V3 Link Aggregation Port Mirroring Cable Diagnostics Loop Prevention
VLAN	Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs) MTU/Port/Tag VLAN
Transmission Method	Store-And-Forward

OTHERS

OTHERS

Certification	FCC, CE, RoHS
Package Contents	TL-SG108E Power Cord Installation Guide Resource CD Rubber Feet
System Requirements	Microsoft® Windows® for running Utility
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing
Warranty	Limited 3-Year Warranty For further information on our warranty policy please visit: http://www.tp-link.com.au/support/rma

About Us

[Corporate Profile](#)
[Contact Us](#)

Press

[News](#)
[Awards](#)
[Security Advisory](#)
[Upcoming Exhibitions](#)

Where to Buy

[Distributor](#)
[Retail](#)
[Reseller](#)
[ISP](#)
[Online Stores](#)

Promotions

Learning Center

[Technology Library](#)

Join TP-Link Community

Follow Us