

HARDWARE FEATURES

Standards and Protocols	IEEE 802.3i/802.3u/ 802.3ab/802.3x
Interface	8 10/100/1000Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX
Fan Quantity	Fanless
Power Consumption	Maximum: 4.63W (220V/50Hz)
External Power Supply	External Power Adapter (Output: 9VDC/0.6A)
Jumbo Frame	15 KB
Switching Capacity	16 Gbps
Dimensions (W x D x H)	7.1 * 3.5 * 1.0 in. (180 * 90 * 25.5 mm)

SOFTWARE FEATURES

Transfer Method	Store and Forward
MAC Address Table	4K
Advanced Functions	Green Technology, saving power up to 80% 802.3X Flow Control, Back Pressure

OTHERS

Certification	FCC, CE, RoHs
Package Contents	8-Port Gigabit Desktop Switch TL-SG1008D Power Adapter Installation Guide
System Requirements	
Environment	Operating Temperature: 0°C~40°C (32°F~104°F); Storage Temperature: -40°C~70°C (-40°F~158°F); Operating Humidity: 10%~90% non-condensing; Storage Humidity: 5%~90% non-condensing
Warranty	Limited 3-Year Warranty For further information on our warranty policy please visit: http://www.tp-link.com.au/support/rma

About Us

Corporate Profile
Contact Us

Press

News
Awards
Security Advisory
Upcoming Exhibitions

Where to Buy

Distributor
Retail
Reseller
ISP
Online Stores

Promotions

Learning Center

Technology Library

Join TP-Link Community

Follow Us

Australia / English

Copyright © 2017 TP-Link Technologies Co., Ltd. All rights reserved.